

Data sheet

Drying Oven SLW 75 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment.
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download


TECHNICAL DATA

| | |
|--------------------------|--|
| air convection | forced |
| chamber capacity [l] /1/ | 76 |
| working capacity [l] | 75 |
| controller | microprocessor with external LCD graphic display |
| display | 7" full colour touch screen |

TEMPERATURE

| | |
|---------------------------------------|---|
| temperature range [°C] | +5°C above ambient temperature ... +300°C |
| temperature resolution every ... [°C] | 0,1 |
| over temperature protection | class 3.1 to DIN 12880 |

| CHAMBER | |
|-----------------------|---|
| door type | solid / door with viewing window (option) |
| interior | |
| Smart PRO | acid-proof stainless steel to DIN 1.4301 |
| IG Smart PRO | acid-proof stainless steel to DIN 1.4301 |
| housing | |
| Smart PRO | powder coated sheet |
| IG Smart PRO | stainless steel linen finish |
| overall dims [mm] /2/ | |
| width A | 590 |
| height B | 850 |
| depth C | 620 |
| Internal dims [mm] | |
| width D | 400 |
| height E | 530 |
| depth F | 360 |



| | |
|-------------------------------------|--------|
| shelves (standard / max) | 2 // 5 |
| max shelf workload [kg] /5/ | 25 |
| - reinforced shelf version (PW) /3/ | 50 |
| max unit workload [kg] | 40 |
| - reinforced unit version (W) /4/ | 80 |
| weight [kg] | 60 |


| ELECTRICAL PARAMETERS | |
|-----------------------|-------------------|
| voltage* | 230V 50Hz |
| nominal power [W] | 1700 |
| warranty | 24 months |
| manufacturer | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

* - 230V 60Hz, 115V 60Hz also available

- 1 - working capacity of chamber can be smaller
- 2 - depth doesn't include 50 mm of power cable
- 3 - reinforced shelf
- 4 - reinforced version
- 5 - on uniformly loaded surface

OPTIONS AND ACCESSORIES



Order number: */A

Door with viewing window



Order number: */P INOX

Stainless steel wire shelf




Order number: */PP

Perforated shelf



Order number: */PW

Reinforced shelf




Order number: KUW GN*/*

Stainless steel cuvettes



Order number: QLK*

Wheels



Order number: */S or */S INOX

Table with wheels



Order number: */ST or */S INOX

Table with wheels




Order number: */W

Reinforced version



Order number: OWW/OWW LED

Interior lighting



Order number: PT 100

Additional temperature sensor



Order number: HEPA

HEPA - fresh air filter



Order number: OCZ/N

Non-standard access port for external sensor



Order number LabDesk

LabDesk - software



Order number: BRT*/L or IQ/OQ/PQ

Calibration and IQ, OQ, PQ qualification