

# Data sheet

## Drying Oven SLW 750 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

### Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download


#### TECHNICAL DATA

air convection	forced
chamber capacity [l] /1/	749
working capacity [l]	749
controller	microprocessor with external LCD graphic display
display	7" full colour touch screen

#### TEMPERATURE

temperature range [°C]	+5°C above ambient temperature ... +300°C
temperature resolution every ... [°C]	0,1
over temperature protection	class 3.1 to DIN 12880

CHAMBER	
door type	solid / door with viewing window (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish
overall dims [mm] /2/	
width A	1260
height B	1600
depth C	870
Internal dims [mm]	
width D	1040
height E	1200
depth F	600



shelves (standard / max)	5 // 16
max shelf workload [kg] /5/	-
- reinforced shelf version (PW) /3/	100
max unit workload [kg]	140
- reinforced unit version (W) /4/	300
weight [kg]	260

ELECTRICAL PARAMETERS	
voltage*	400 3/N
nominal power [W]	5500
warranty	24 months
manufacturer	POL-EKO-APARATURA

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

OPTIONS AND ACCESSORIES



Order number: \*/A

Door with viewing window



Order number: \*/P INOX

Stainless steel wire shelf




Order number: \*/PP

Perforated shelf



Order number: \*/PW

Reinforced shelf



Order number: KUW GN\*/\*

Stainless steel cuvettes




Order number: \*/W

Reinforced version



Order number: OWW/OWW LED

Interior lighting




Order number: PT 100

Additional temperature sensor



Order number: HEPA

HEPA - fresh air filter



Order number: OCZ/N

Non-standard access port for external sensor



Order number LabDesk

LabDesk - software



Order number: BRT\*/L or IQ/OQ/PQ

Calibration and IQ, OQ, PQ qualification