

## Lab-Jacks, aluminium



New design and improved construction:

- Improved scissor technology with reduced tolerances
- Ergonomic knob, rounded and user friendly
- Scissor-construction made of 18/10-stainless steel

Properties:

- All models are manufactured according to DIN 12897.
- With the operating load we differ between the maximal dynamic operating load (Kg max. dyn.) and the maximal static operating load (Kg max. stat.) of the lab jack. These norms are also according to DIN 12897.
- Smaller models up to 240x240mm (Typ 1) have a simple adjusting wheel, which can be operated by hand.
- With the bigger models from 300x300mm on (Typ 2) we recommend the use of a ratchet, which connects with a special adjusting wheel. The ratchet is included.

Material	A (Length)	B (Width)	C min	C max	Kg max dyn	Kg max stat	Type	Thread	Article no.
Al green	100	100	55	120	5	10	1	M6 x 1,00	11015
Al green	160	130	60	275	7	30	1	M8 x 1,25	11020
Al green	200	200	60	275	7	30	1	M8 x 1,25	11030
Al green	240	240	60	275	7	30	1	M8 x 1,25	11040
Al green	300	300	90	470	12	60	2	M12 x 1,75	11080
Al green	400	400	90	470	15	60	2	M12 x 1,75	11090
Ratchet	190	.	.	.	.	.	.	.	11088