

Lovibond® Water Testing

Tintometer® Group



TC 135 S



- Temperature range 2 °C to 40 °C, adjustable in steps of 0.1 °C
- Low power consumption
- Illuminated LED display of preset and current temperatures
- Ideal for BOD determination at 20 °C

Part Number: 2438200

Versatile in use

Our thermostatically controlled cabinets are the means of choice both for temperature-controlled storage of samples and for BOD determination in waste water analysis. The integral temperature control unit meets EMC directive IEC 61326 ("Electrical devices for measurement, monitoring and for use in laboratories").

Continuous temperature control

The thermostat cabinets allow continuous temperature control. Over a range of 2-40 °C the temperature can be set in steps of 0.1 °C.

Internal power connections

The use of external devices is no problem thanks to several sockets installed in the interior.

Energy efficiency

The highly efficient components and reinforced insulation provide low consumption values.

Variable

You can choose between 4 models with steel door (135, 255 and 445 l net capacity) and 2 models with glass door (140 and 235 l net capacity).

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | Oil and Gas | Pharmaceutical Industry | Power and Energy

TC 135 S

Perfect for a number of different applications in industry and research. The temperature of the thermostatically controlled cabinets can be regulated individually in the smallest of steps - and an LED display keeps the status quo under control at all times. There are six models available with different useful contents and glass or steel doors.

Technical Data

Display	Backlit LED display
Power Supply	220 - 240 V / 50 Hz
Net Capacity	135 L
Consumption	approx. 1,41 kWh/ 24h
Climate Class	SN, + 10 °C to + 32 °C
Coolant	R600a
Sockets	4
Temperature Range	+ 2 °C to + 40 °C, steps of 0,1 °C
Temperature Tolerance	± 1 °C, specified for a stirred 500 ml water sample. For BOD (T=20 °C ±0,5 °C)
Storage Space	3 metal grids
Shelf Loading Capacity	45 kg
Suitable to build under	Yes
Further Equipment	Standard Door
Dimensions Internal	513 x 702 x 441 mm

Dimensions without 600 x 819 x 600 mm

Work Top

Compliance CE

Dimensions 600 x 850 x 600 mm

Weight 39 kg

Accessories

Title	Part Number
Temperature control unit for TC 135 S, TC 140 G	2428201-2
Wooden box for TC 135 S, TC 140 G (IPPC Standard - ISPM15)	425768
Metal grid for TC 135 S, TC 140 G	425791
Spare board for temperature control unit	427542

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
Fax: +49 (0)231/94510-30
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.com
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies